

SAE 10W-40 Motor Oil

Version: 1.7	Revision Date: 12/12/2019		Print Date: 08/03/2022	
29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION				
Product identifier Trade name Product code	: SAE 10W Motor Oil : 898390			
Relevant identified uses of the substance or mixture and uses advised against Recommended use : Motor Oil				
Details of the supplier of the sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (US 1-800-TEAMVAL (1-800-832-	A)	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)		

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

SDS@valvoline.com

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM),	64742-54-7	Not a hazardous	>=90.00 - <=



Version: 1.7

SAFETY DATA SHEET

SAE 10W-40 Motor Oil

Print Date:

			08/03/2022
HYDROTREATED HEAVY PARAFFINIC		substance or mixture.	100.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.50 - < 5.00

Revision Date: 12/12/2019

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASUR	ES
General advice	: No hazards which require special first aid measures.
If inhaled	 If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	 Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical 	
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or wat courses.	er
Hazardous combustion products	: Ketones formaldehyde	



SAE 10W-40 Motor Oil

Version: 1.7	Revision Date: 12/12/2019	Print Date: 08/03/2022
	Aldehydes acrolein Hydrocarbons carbon dioxide and carbon monoxide	
Specific extinguishing methods	:	
	Product is compatible with standard fire-fig	hting agents.
Further information	: Standard procedure for chemical fires.	
Special protective equipment for firefighters	: In the event of fire, wear self-contained bre	eathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.	ł
Environmental precautions	: Prevent further leakage or spillage if safe to do so.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	
Other information	: Comply with all applicable federal, state, and local regulations	

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components		(Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM),	64742-54-7	TWA	5 mg/m3	OSHA Z-1



SAE 10W-40 Motor Oil

Version: 1.7

Revision Date: 12/12/2019

Print Date: 08/03/2022

HYDROTREATED HEAVY PARAFFINIC			Mist	
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Engineering measures	conditions of exist, provide exhaust) ven guidelines (if	use. Howeve sufficient me tilation to mair	hould be adequate for n er, if unusual operating c chanical (general and/o ntain exposure below ex below levels that cause erse effects.	conditions r local (posure
Personal protective equipmen Respiratory protection		respiratory pro	otective equipment norm	nally
Eye protection		Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.		
Skin and body protection	: Wear as app Safety shoes Wear resista supplier).	S	sult your safety equipm	ent
Hygiene measures	: General indu	ustrial hygiene	practice.	



SAE 10W-40 Motor Oil

Version: 1.7	Revision Date: 12/12/2019

Print Date: 08/03/2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	amber
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	570.00 °F / 298.89 °C (1013.33 hPa)
Flash point	:	394 - 480 °F / 201 - 249 °C
		Method: Cleveland open cup
Evaporation rate	:	1 Ethyl Ether
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8690 g/cm3 (60.01 °F / 15.56 °C)
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available



SAE 10W-40 Motor Oil

Version: 1.7	Revision Date: 12/12/2019	Print Date: 08/03/2022
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: 104 mm2/s (104 °F / 40 °C)	
Oxidizing properties	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Inhalation Skin contact Eye Contact Ingestion Acute toxicity Not classified based on availa Components:	
DISTILLATES (PETROLEUN	I), HYDROTREATED HEAVY PARAFFINIC:
•	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
Skin corrosion/irritation	
Not classified based on availa	ble information.
Components:	
DISTILLATES (PETROLEUN	I), HYDROTREATED HEAVY PARAFFINIC:
Assessment	: Slight, transient irritation
Result	: Slight, transient irritation



Version: 1.7

SAE 10W-40 Motor Oil

Print Date:

SION: 1.7	Revision Date: 12/12/2019	08/03/2022
HYDROTRE	ATED LIGHT PARAFFINIC DISTILLATE:	
Assessment		
Result	: Slight, transient irritation	
Serious eye	e damage/eye irritation	
Not classified Product:	d based on available information.	
Remarks	: Unlikely to cause eye irritation or injury.	
Component		
DISTILLATE	ES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	:
Result	: No eye irritation	
Assessment	: No eye irritation	
	ATED LIGHT PARAFFINIC DISTILLATE:	
Result	: Slight, transient irritation	
Assessment	: Slight, transient irritation	
	or skin sensitisation	
Skin sensiti		
	d based on available information.	
Not classifie	d based on available information.	
	nutagenicity	
	d based on available information.	
Carcinogen		
Component	d based on available information.	
	3. ES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	:
Carcinogenio		
Assessment		
HYDROTRE	ATED LIGHT PARAFFINIC DISTILLATE:	
Carcinogenio	city - : Classified based on DMSO extract cont	ent < 3% (Regulation
Assessment	(EC) 1272/2008, Annex VI, Part 3, Note	e L)
IARC	No component of this product present at levels greater that	
	identified as probable, possible or confirmed human carcir	nogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is	
	on OSHA's list of regulated carcinogens.	
NTP	No component of this product present at levels greater that	an or equal to 0.1% is
	identified as a known or anticipated carcinogen by NTP.	
Reproductiv		
Not classifie	d based on available information.	

Revision Date: 12/12/2019

Not classified based on available information.

STOT - single exposure

Not classified based on available information.



SAE 10W-40 Motor Oil

Version: 1.7

Revision Date: 12/12/2019

Print Date: 08/03/2022

STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information.

<u>Product:</u> No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC: No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information <u>Product:</u> Remarks

: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Short-term (acute) aquatic hazard	:	Not classified based on available information.
Long-term (chronic) aquatic hazard	:	Not classified based on available information.
<u>Components:</u> DISTILLATES (PETROLEUM) Toxicity to fish		YDROTREATED HEAVY PARAFFINIC: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
Ecotoxicology Assessment		



SAE 10W-40 Motor Oil

Version: 1.7	Revision Date: 12/12/2019	Print Date: 08/03/2022
Short-term (acute) aquatic hazard	: Not classified based on available information.	
Long-term (chronic) aquatic hazard	: Not classified based on available information.	
Persistence and degradabil <u>Components:</u> No data available Bioaccumulative potential <u>Components:</u> DISTILLATES (PETROLEUM Partition coefficient: n- octanol/water No data available Mobility in soil	1), HYDROTREATED HEAVY PARAFFINIC:	
Components: No data available Other adverse effects No data available <u>Product:</u> Additional ecological information Components:	: No data available	
SECTION 13. DISPOSAL CONSI	DERATIONS	

Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good



SAE 10W-40 Motor Oil

Version: 1.7

Revision Date: 12/12/2019

Print Date: 08/03/2022

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

California Prop. 65

MARNING: Cancer - www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:				
DSL	•	All components of this product are on the Canadian DSL		
AICS	:	On the inventory, or in compliance with the inventory		
ENCS	:	q (quantity restricted)		
KECI	:	On the inventory, or in compliance with the inventory		
PICCS	:	On the inventory, or in compliance with the inventory		
IECSC	:	On the inventory, or in compliance with the inventory		
TCSI	:	On the inventory, or in compliance with the inventory		
TSCA	:	On TSCA Inventory		

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.



SAE 10W-40 Motor Oil

Version: 1.7

Revision Date: 12/12/2019

Print Date: 08/03/2022


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : R0164091



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).



SAE 10W-40 Motor Oil

Version: 1.7	Revision Date: 12/12/2019	Print Date: 08/03/2022
List of abbreviatior sheet :	ns and acronyms that could be, but not necessarily are, used	d in this safety data
	Conference of Industrial Hygienists	
CAS : Chemical Al CMR : Carcinogen	bstracts Service (Division of the American Chemical Society ic, Mutagenic or Toxic for Reproduction	·).
FG : Food grade GHS : Globally Ha H-statement : Haza	rmonized System of Classification and Labeling of Chemica ard Statement	ls.
	al Air Transport Association. erous Goods Regulation by the "International Air Transport /	Association" (IATA).
ICAO-TI (ICAO): IMDG : Internation	al Civil Aviation Organization Technical Instructions by the "International Civil Aviation Org al Maritime Code for Dangerous Goods Organization for Standardization	ganization"
logPow : octanol-w LCxx : Lethal Cond	vater partition coefficient centration, for xx percent of test population	
	e, for xx percent of test population. oncentration for xx of a substance oncentration of xx	
N.O.S.: Not Otherv OECD : Organizati OEL : Occupationa	ion for Economic Co-operation and Development	
P-Statement : Pred PBT : Persistent , I	cautionary Statement Bioaccumulative and Toxic	
STEL : Short-term	otective Equipment exposure limit arget Organ Toxicity	
TLV : Threshold Li TWA : Time-weigh	imit Value ited average	
vPvB : Very Persis WEL : Workplace I	stent and Very Bioaccumulative Exposure Level	
DOT : Department		bility Act
HMIRC : Hazardou	secticide, Fungicide, and Rodenticide Act us Materials Information Review Commission Materials Identification System	
NFPA : National Fi NIOSH : National I	ire Protection Association Institute for Occupational Safety and Health	
	nal Safety and Health Administration nada Pest Management Regulatory Agency	

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System