

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Roberts 3000 M/P Carpet & Sheet Vinyl Adhesive
 Roberts MSDS Code # 3000C
 PRODUCT USES: For installing a wide variety of floorcovering materials

W.M.I.S. CLASSIFICATION: NON-CONTROLLED
 V.O.C. CONTENT: 0 Calculated

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD.
 ADDRESS: 2070 Steeles Ave. Bramalea, Ontario L6T 1A7
 24 HOUR (CANUTEC) PHONE: (613) 996-6666
 DATE REVISED: December 01/06

NAME OF PREPARER: Technical Dept.
 INFORMATION PHONE: (905) 791-4444
 SOURCES USED: Raw material supplier M.S.D.S.

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS					

SECTION III - PHYSICAL DATA

BOILING POINT: 100° C FREEZING POINT: N/A
 VAPOUR DENSITY (AIR=1): Heavier than air
 VAPOUR PRESSURE (MM OF MERCURY): N/A
 SOLUBILITY IN WATER: Miscible
 APPEARANCE AND ODOUR: Beige, soft buttery paste, slight odour.

SPECIFIC GRAVITY (H2O=1): 1.28 pH: 9.2 - 9.8
 EVAPORATION RATE (BUTYL ACETATE=1): Slower
 EVAPORATION RATE (ETHYL ACETATE=1): Slower
 PERCENT VOLATILE: 46
 ODOUR THRESHOLD (PPM): Not available

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): Over 200°F
 FLAMMABLE LIMITS (% BY VOLUME):
 FIRE EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical
 SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None

METHOD USED: P.M.C.C.
 LOWER: N/A UPPER: N/A
 AUTO IGNITION TEMP: N/A
 IMPACT SENSITIVITY: Insensitive
 SENSITIVITY TO STATIC DISCHARGE: Insensitive
 TDG FLAMMABILITY CLASSIFICATION: Not regulated.

SECTION V - REACTIVITY DATA

STABILITY: Stable
 INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, and Hydrocarbons upon combustion.
 HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Excessive Heat
 CONDITIONS TO AVOID: None

SECTION VI - TOXICOLOGICAL PROPERTIES

ENTRY ROUTE TABLE

SKIN CONTACT	X	SKIN ABSORPTION	EYE CONTACT	X	INHALATION ACUTE	X	INHALATION CHRONIC	INGESTION	X
--------------	---	-----------------	-------------	---	------------------	---	--------------------	-----------	---

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion causes vomiting, diarrhea, depressed respiration.
 EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

LD50 (SPECIFY SPECIES & ROUTE): Not available	LC50 (SPECIFY SPECIES): Not available	EXPOSURE LIMIT: N/A	IRRITANCY: Eye and skin.
SENSITIZING CAPACITY: None known	CARCINOGENICITY: None	REPRODUCTIVITY EFFECTS: None known	SYNERGISTIC MATERIALS: None known

SECTION VII - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): Not required under normal conditions of use.
 VENTILATION: General dilution ventilation.
 PROTECTIVE GLOVES: Rubber gloves should be worn.
 OTHER PROTECTIVE EQUIPMENT: None required.
 EYE PROTECTION: Goggles / glasses with side shields
 SPILL PROCEDURES: Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.
 WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.
 STORAGE & HANDLING PRECAUTIONS: Store in ventilated area as close to 70°F as possible.
 OTHER PRECAUTIONS: Keep containers closed when not in use. Keep out of reach of children.

SECTION VIII - FIRST AID MEASURES

EYES: Flush with water for 20 minutes holding eyelids open. Obtain medical attention immediately.
 SKIN: Wash with soap and water. Remove dried adhesive with mineral spirits followed by soap and water. Remove contaminated clothing and launder before re-use. Consult physician if irritation develops.
 INGESTION: Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Contact physician immediately.